

## Page 1 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

Print Date 2014/08/30

Version 3.1

MSDS code: MCAC100

Revision date / valid from 2014/08/30

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Damp Clear 500g Moisture Trap, 2x500g Refill, 5x500g Refill

 Substance name
 : calcium chloride

 Index-No.
 : 017-013-00-2

 CAS-No.
 : 10043-52-4

 EC-No.
 : 233-140-8

Registration number : 01-2119494219-28-xxxx

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the : At this time we do not yet have information on identified uses. Substance/Mixture : They will be included in this safety data sheet when available.

Uses advised against : At this moment we have not identified any uses advised

against

#### 1.3. Details of the supplier of the safety data sheet

Company : Kilrock Products Ltd

Unit 1B, Alma Road Industrial Estate

Chesham, Bucks, HP5 3HB

Telephone : +44 (0) 1494 793 900
Telefax : +44 (0) 1494 793 400
E-mail address : info@kilrock.co.uk

#### 1.4. Emergency telephone number

Emergency telephone : Mr. R. Davis

number +44 (0) 7836526420

#### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

REGULATION (EC) No 1272/2008			
Hazard class	Hazard category	Target Organs	Hazard statements
Serious eye damage/eye irritation	Category 2		H319



# Page 2 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### Classification according to EU Directives 67/548/EEC or 1999/45/EC

Directive 67/548/EEC or 1999/45/EC		
Hazard symbol / Category of danger Risk phrases		
Irritant (Xi)	R36	

For the full text of the R-phrases mentioned in this Section, see Section 16.

#### Most important adverse effects

Human Health : See section 11 for toxicological information.

Physical and chemical : So

hazards

Potential environmental

effects

See section 9 for physicochemical information.

See section 12 for environmental information.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No 1272/2008

Hazard symbols



Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements

Prevention : P264 Wash hands thoroughly after handling.

P280 Wear eye protection/ face protection.

Response : P305 + P351 + P338 IF IN EYES: Rinse cautiously with

water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

#### Hazardous components which must be listed on the label:

· calcium chloride

#### 2.3. Other hazards



## Page 3 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

For Results of PBT and vPvB assessment see section 12.5.

#### **Section 3: Composition/information on ingredients**

#### 3.1. Substances

Haza	rdous components	Amount [%]	Classifi (REGULATION (EG Hazard class / Hazard category		Classification (67/548/EEC)
calcium chlo Index-No. CAS-No. EC-No. Registration	ride : 017-013-00-2 : 10043-52-4 : 233-140-8 : 01-2119494219-28-xxxx	>= 77 - <= 100	Eye Irrit.2	H319	Irritant; Xi; R36

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

General advice : Take off contaminated clothing and shoes immediately.

If inhaled : Remove to fresh air. If symptoms call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water. If skin

irritation persists, call a physician.

In case of eye contact : Consult an eye specialist immediately. Rinse immediately with

plenty of water, also under the eyelids, for at least 10 minutes.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Do

NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects

and symptoms.

Effects : See Section 11 for more detailed information on health effects

and symptoms.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

#### **Section** 5: Firefighting measures



## **Page 4 of 15 MATERIAL SAFETY DATA SHEET**



#### FIBERTECH DAMPSORB & REFILL

#### **Extinguishing media**

Suitable extinguishing

media

The product itself does not burn. Use extinguishing measures

that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing

media

No information available.

#### Special hazards arising from the substance or mixture

Specific hazards during

firefighting

In case of fire hazardous decomposition products may be

produced such as: Hydrogen chloride gas

#### 5.3. Advice for firefighters

Special protective

equipment for firefighters

In the event of fire, wear self-contained breathing

apparatus. Wear appropriate body protection (full protective

suit)

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

#### Section 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Avoid dust formation.

Provide adequate ventilation. Avoid contact with skin and

eyes. Do not breathe dust.

#### **Environmental precautions**

Environmental

precautions

: Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and materials for containment and cleaning up

containment and cleaning

up

Methods and materials for : Use mechanical handling equipment. Keep in suitable, closed

containers for disposal.

Further information : Treat recovered material as described in the section "Disposal

considerations".

#### Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on personal protective equipment.

See Section 13 for waste treatment information.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling



## **Page 5 of 15 MATERIAL SAFETY DATA SHEET**



#### FIBERTECH DAMPSORB & REFILL

: Keep container tightly closed. Use personal protective Advice on safe handling

> equipment. Avoid contact with skin, eyes and clothing. Avoid dust formation. Emergency eye wash fountains and emergency

showers should be available in the immediate vicinity.

: Keep away from food, drink and animal feedingstuffs. Smoking, Hygiene measures

> eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of workday. Take off

all contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Store in original container.

areas and containers

Advice on protection

against fire and explosion

: The product is not flammable. Normal measures for preventive

fire protection.

Further information on

storage conditions

: Keep tightly closed in a dry and cool place. Product is

hygroscopic.

Advice on common

storage

: Keep away from food, drink and animal feedingstuffs.

Materials to avoid: Strong oxidizing agents

7.3. Specific end use(s)

> Specific use(s) : No information available.

#### **Section** 8: Exposure controls/personal protection

#### **Control parameters**

#### **Other Occupational Exposure Limit Values**

(Additional) Information

Contains no substances with occupational exposure limit values.

Contains no substances with occupational exposure limit values.

**Component:** calcium chloride CAS-No.

10043-52-4

#### Derived No Effect Level (DNEL)/Derived Minimal Effect Level (DMEL)

**DNEL** 

Industrial use, Acute effects, Inhalation 10 mg/m3

**DNEL** 

Industrial use, Inhalation 5 mg/m3

Long-term exposition

DNEL

Professional use, Inhalation 5 mg/m3

Long-term exposition



# Page 6 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

**DNEL** 

Professional use, Acute effects, Inhalation : 10 mg/m3

**DNEL** 

Consumer use, Acute effects, Inhalation : 5 mg/m3

**DNEL** 

Consumer use, Inhalation : 2.5 mg/m3

Long-term exposition

#### **Predicted No Effect Concentration (PNEC)**

Soil and plants : 150 g/m<sup>2</sup>

A tentative "PNEC", a so-called "no-effect-

deposition"(NEdep) was derived for the exposure route for deposition of calcium via road salts or dust suppressors. It should be noted, that although the units refer to exposure via air, this value reflects effects caused by CaCl2 deposited from air into soil or onto a plants' surface.

Sensitive terrestrial plants : 215 mg/kg

#### 8.2. Exposure controls

#### **Appropriate engineering controls**

Refer to protective measures listed in sections 7 and 8.

#### Personal protective equipment

Respiratory protection

Advice : Required if dust is released

Recommended Filter type:

Particle filter:P2 Particle filter:P3

Hand protection

Advice : Wear suitable gloves.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace

conditions (mechanical strain, duration of contact).

Protective gloves should be replaced at first signs of wear.

Material : natural rubber

Break through time : >= 8 h Glove thickness : 0.5 mm

Material : butyl-rubber
Break through time : >= 8 h
Glove thickness : 0.5 mm



# Page 7 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

Material : polychloroprene

Break through time : >= 8 h Glove thickness : 0.5 mm

Material : Nitrile rubber
Break through time : >= 8 h
Glove thickness : 0.35 mm

Material : Fluorinated rubber

Break through time : >= 8 h Glove thickness : 0.4 mm

Material : Polyvinylchloride

Break through time : >= 8 h
Glove thickness : 0.5 mm

Eye protection

Advice : Safety glasses

Skin and body protection

Advice : Wear suitable protective clothing.

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

#### **Section** 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Form : solid

Colour : white

Odour : odourless

Odour Threshold : no data available

pH : 9 - 10.5 (100 g/l; 20 °C)

Melting point/range : 782 °C

Boiling point/boiling range : 1,600 °C

Flash point : not applicable

Evaporation rate : no data available



# Page 8 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : no data available

Lower explosion limit : no data available

Vapour pressure : no data available

Relative vapour density : no data available

Density : 2.15 g/cm3 (20 °C)

Water solubility : 745 g/l (20 °C)

Partition coefficient: n-octanol/water : no data available

Auto-ignition temperature : not applicable

Thermal decomposition : no data available

Viscosity, dynamic : no data available

Explosivity : Product is not explosive.

Oxidizing properties : no data available

9.2. Other information

Molecular weight : 110.98 g/mol

Bulk density : ca. 1000 kg/m3

Section 10: Stability and reactivity

10.1. Reactivity

Advice : No decomposition if used as directed.

10.2. Chemical stability

Advice : No decomposition if stored and applied as directed.

10.3. Possibility of hazardous reactions

Hazardous reactions : No information available.

10.4. Conditions to avoid

Conditions to avoid : Water

10.5. Incompatible materials



## **Page 9 of 15 MATERIAL SAFETY DATA SHEET**



#### FIBERTECH DAMPSORB & REFILL

Materials to avoid : Alkaline earth metals, Alkali metals

#### 10.6. Hazardous decomposition products

products

Hazardous decomposition : In case of fire hazardous decomposition products may be

produced such as: Hydrogen chloride gas

#### **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity			
	Oral		
	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.	I	
	Inhalation		
	Product dust may be irritating to respiratory system. High concentration may cause difficulty in breathing.		
	Dermal		
	Please find this information in the listing of the component/components below in the MSDS.		
	Irritation		
	Skin		
Result	: No skin irritation		
	Eyes		
Result	: Risk of serious damage to eyes.		
	Sensitisation		
Result	: No sensitizing effect known.		
	CMR effects		
CMR Properties			
Carcinogenicity	: Please find this information in the listing of the component/components below in the MSDS.		
Mutagenicity	: Please find this information in the listing of the component/components below in the MSDS.		
54805 / Version 3.1	9/15		



# Page 10 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

Teratogenicity : Please find this information in the listing of the

component/components below in the MSDS.

Reproductive toxicity : Please find this information in the listing of the

component/components below in the MSDS.

Specific Target Organ Toxicity

Single exposure

remark : The substance or mixture is not classified as specific target organ

toxicant, single exposure.

Repeated exposure

remark : The substance or mixture is not classified as specific target organ

toxicant, repeated exposure.

Other toxic properties

**Aspiration hazard** 

No aspiration toxicity classification

Component: calcium chloride CAS-No. 10043-52-4

10045-32-4

Acute toxicity

Oral

LD50 Oral : 2301 mg/kg (rat) (OECD Test Guideline 401)

Dermal

LD50 Dermal : > 5000 mg/kg )

Irritation

Skin

Result : No skin irritation (rabbit) (OECD Test Guideline 404)

**Eyes** 

Result : Irritating to eyes. (rabbit) (OECD Test Guideline 405)

Sensitisation



# Page 11 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

Result : The product is not expected to cause hypersensitivity.

**CMR** effects

**CMR Properties** 

Mutagenicity : Did not show mutagenic effects in animal experiments.

Teratogenicity : Did not show teratogenic effects in animal experiments.

Reproductive toxicity : No toxicity to reproduction

Carcinogenicity

It dissociates into ions that are present physiologically in relatively high levels in vertebrates. Therefore, a study is considered

(scientifically) unnecessary.

Reproductive toxicity

NOAEL Parent 169 mg/kg

(rabbit)

(OECD Test Guideline 414)

Animal testing did not show any effects on fertility.

Other toxic properties

Repeated dose toxicity

It dissociates into ions that are present physiologically in relatively high levels in vertebrates. Therefore, a study is considered

(scientifically) unnecessary.

#### **Section 12: Ecological information**

#### 12.1. Toxicity

Component:	calcium chloride	CAS-No. 10043-52-4	
	Acute toxicity		
Fish			
LC50	LC50 : 4630 mg/l (Pimephales promelas (fathead minnow); 96 h)		
Toxicity to daphnia and other aquatic invertebrates			



# Page 12 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

LC50	: 2400 mg/l (Daphnia magna; 48 h) (OECD Test Guideline 202)	
	algae	
EC50	<ul> <li>2900 mg/l (Pseudokirchneriella subcapitata (green algae); 72 h)</li> <li>(OECD Test Guideline 201)</li> </ul>	
Chronic toxicity		
Fish		
study scientifically unjustified		
Aquatic invertebrates		

study scientifically unjustified

Component:	calcium chloride	CAS-No. 10043-52-4	
Persistence and degradability			
Persistence			
Result	: not applicable		
Biodegradability			
Result	: The methods for determining the		

#### 12.3. Bioaccumulative potential

12.2. Persistence and degradability

Component:	calcium chloride	CAS-No. 10043-52-4
Bioaccumulation		

Result : Bioaccumulation is not expected.

#### 12.4. Mobility in soil

Component:	calcium chloride	CAS-No.
		10043-52-4



### Page 13 of 15 **MATERIAL SAFETY DATA SHEET**



#### FIBERTECH DAMPSORB & REFILL

#### Mobility

no data available

#### 12.5. Results of PBT and vPvB assessment

Component:	calcium chloride	CAS-No. 10043-52-4
Results of PBT and vPvB assessment		

This substance is not considered to be persistent, bioaccumulating Result

nor toxic (PBT)., This substance is not considered to be very

persistent nor very bioaccumulating (vPvB).

#### 12.6. Other adverse effects

#### Additional ecological information

Result : Do not flush into surface water or sanitary sewer system.

#### **Section 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product Disposal together with normal waste is not allowed. Special

> disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services.

Contaminated packaging Empty contaminated packagings thoroughly. They can be

recycled after thorough and proper cleaning. Packagings that cannot be cleaned are to be disposed of in the same manner

as the product.

European Waste Catalogue Number

No waste code according to the European Waste Catalogue can be assigned for this product, as the intended use dictates

the assignment. The waste code is established in consultation

with the regional waste disposer.

#### **Section 14: Transport information**

Not dangerous goods for ADR, RID, IMDG and IATA.

#### 14.1. UN number

Not applicable.



# Page 14 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

Not applicable.

#### 14.4. Packaging group

Not applicable.

#### 14.5. Environmental hazards

Not applicable.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG : Not applicable.

#### **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UK ISR : calcium chloride: Annual reporting level threshold: 10,000 kg

Other regulations : Occupational restrictions: Take note of Dir 92/85/EEC on the

safety and health of pregnant workers at work and of Dir 94/33/EC on the protection of young people at work.

.

#### **Notification status**

calcium chloride:

Regulatory List	Notification	Notification number
AICS	YES	
DSL	YES	
INV (CN)	YES	
ENCS (JP)	YES	(1)-176
ISHL (JP)	YES	(1)-176
TSCA	YES	
EINECS	YES	233-140-8
KECI (KR)	YES	KE-04496
PICCS (PH)	YES	

#### 15.2. Chemical Safety Assessment

no data available



# Page 15 of 15 MATERIAL SAFETY DATA SHEET



#### FIBERTECH DAMPSORB & REFILL

#### **Section 16: Other information**

Full text of R-phrases referred to under sections 2 and 3.

R36 Irritating to eyes.

Full text of H-Statements referred to under sections 2 and 3.

H319 Causes serious eye irritation.

#### **Further information**

Other information : The information provided in this Safety Data Sheet is correct to

our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements

and is not to be considered as a warranty or quality specification and does not constitute a legal relationship. The information contained in this Safety Data Sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material

or in any process, unless specified in the text

|| Indicates updated section.