



MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



Revision date: 20/07/2018
Revision: 4
Supersedes date: 07/10/2014

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Excel Industries Stove Glass Cleaner
Container size 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Glass cleaner.

1.3. Details of the supplier of the safety data sheet

Supplier Excel Industries
Coolmine Industrial Estate
Clonsilla Road
Dublin 15
Tel: 00 353 1811 8701
Fax: 00 353 1811 8785

1.4. Emergency telephone number

Emergency telephone Excel Industries: 00 353 1811 8701 (Mon-Fri: 09:00-17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229
Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**MATERIAL SAFETY DATA SHEET****STOVE CARE GLASS CLEANER****Contains**

ISOPROPANOL

Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTRE/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product is not identified as a PBT substance.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

ISOPROPANOL			10-30%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-0000	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS			5-10%
<0.1% 1,3 BUTADIENE			
CAS number: 68476-85-7	EC number: 270-704-2		
Classification Flam. Gas 1 - H220 Press. Gas (Liq.) - H280			
2-BUTOXYETHANOL			5-10%
CAS number: 111-76-2	EC number: 203-905-0	REACH registration number: 01-2119475108-36-XXXX	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319			

MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



AMMONIA ...%			<1%
CAS number: 1336-21-6	EC number: 215-647-6	REACH registration number: 01-2119982985-14-XXXX	
M factor (Acute) = 1			
Classification			
Skin Corr. 1B - H314			
Aquatic Acute 1 - H400			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments CAS 68476-85-7 - Petroleum Gas, The substance contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting.
Skin contact	Wash skin thoroughly with soap and water.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any contact lenses and open eyelids wide apart.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Coughing, chest tightness, feeling of chest pressure.
Ingestion	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause nausea, headache, dizziness and intoxication.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.
Eye contact	Causes serious eye irritation. Profuse watering of the eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Show this safety data sheet to the doctor in attendance.
-----------------------------	----------------------------------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



Specific hazards

Pressurised container: may burst if heated Extremely flammable. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous combustion products

Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions

Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Absorb in vermiculite, dry sand or earth and place into containers. Contain spillage with sand, earth or other suitable non-combustible material.

6.4. Reference to other sections

Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, sparks and open flame. Store in a cool and well-ventilated place. Protect from freezing and direct sunlight.

Storage class

Extremely Flammable Aerosol

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ISOPROPANOL

MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk)

Short-term exposure limit (15-minute): WEL 50 ppm(Sk)

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

ISOPROPANOL (CAS: 67-63-0)

DNEL

Consumer - Oral; Long term systemic effects: 26 mg/kg

Workers - Dermal; Long term systemic effects: 888 mg/kg

Consumer - Dermal; Long term systemic effects: 319 mg/m³

Consumer - Inhalation; Long term systemic effects: 89 mg/m³

Workers - Inhalation; Long term systemic effects: 500 mg/m³

PNEC

- Fresh water; 140.9 mg/l

- Sediment (Freshwater); 552 mg/kg

- Intermittent release; 140.9 mg/l

- Sediment (Marinewater); 552 mg/kg

- Marine water; 140.9 mg/l

- STP; 2251 mg/l

- Soil; 28 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

Personal protection

Wear protective clothing.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166. Provide eyewash station.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. (PE/PA/PE), 2.5mil (0.06mm), >480 min. Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated.



MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



Hygiene measures	Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.
Thermal hazards	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	White foam.
Odour	Slight alcoholic.
Odour threshold	Not determined.
pH	Not determined. Liquid base: pH (concentrated solution): 10.0 ± 0.5
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	A flash point method is not available but the major hazardous component, the Propellant has a flash point of $<-60^{\circ}\text{C}$ with flammability limits of 10.9% vol. upper and 1.4% vol. lower.
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Relative density	0.96 @ 20°C
Solubility(ies)	Miscible with water.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---------------------------------------------------------------------

10.2. Chemical stability

Stability	Highly volatile.
------------------	------------------

10.3. Possibility of hazardous reactions



MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



Possibility of hazardous reactions

No potentially hazardous reactions known. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid

Acids. Oxidising agents.

10.6. Hazardous decomposition products

Oxides

Hazardous decomposition products

Thermal decomposition or combustion products may include the following substances: of carbon. Toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 5,555.56

Acute toxicity - dermal

ATE dermal (mg/kg) 12,222.22

Acute toxicity - inhalation

ATE inhalation (gases ppm) 50,000.0

ATE inhalation (vapours mg/l) 122.22

ATE inhalation (dusts/mists mg/l) 16.67

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause drowsiness or dizziness.

Target organs

Central nervous system Respiratory system, lungs

Toxicological information on ingredients.

ISOPROPANOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,045.0

Species Rat

Notes (oral LD₅₀) 5840 mg/kg, Oral, Rat

ATE oral (mg/kg) 5,045.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 12,800.0

Species Rabbit

MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



Notes (dermal LD ₅₀)	>2000 mg/kg, Dermal, Rabbit
ATE dermal (mg/kg)	12,800.0
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Based on available data the classification criteria are not met.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes serious eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	May cause drowsiness or dizziness.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Toxicological effects	Information given is based on product data, a knowledge of the components and the toxicology of similar products.
<u>Acute toxicity - oral</u>	
Notes (oral LD ₅₀)	Not applicable.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD ₅₀)	Not applicable.
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC ₅₀)	LC ₅₀ >20 mg/l, Inhalation, Rat
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not irritating.
<u>Serious eye damage/irritation</u>	

**MATERIAL SAFETY DATA SHEET****STOVE CARE GLASS CLEANER**

Serious eye damage/irritation	Not irritating.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Not sensitising.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	Carcinogenicity in humans is not expected.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Does not contain any substances known to be toxic to reproduction.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.
<u>Inhalation</u>	
Inhalation	May cause respiratory system irritation.
<u>Skin contact</u>	
Skin contact	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
<u>Route of exposure</u>	
Route of exposure	Inhalation Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which is very toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Ecological information on ingredients.**PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE**

Ecotoxicity Information given is based on product data, a knowledge of the components and the toxicology of similar products.

12.1. Toxicity

Toxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Ecological information on ingredients.

MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



ISOPROPANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: >100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >100 mg/l, Scenedesmus subspicatus

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Toxicity Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.

AMMONIA ...%

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

ISOPROPANOL

Persistence and degradability The product is readily biodegradable.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available.

Ecological information on ingredients.

ISOPROPANOL

Bioaccumulative potential Bioaccumulation is unlikely.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Bioaccumulative potential Bioaccumulation is unlikely.

12.4. Mobility in soil

Mobility The product is miscible with water and may spread in water systems.

Ecological information on ingredients.

ISOPROPANOL

Mobility No data available.



MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Mobility

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment No data available.

Ecological information on ingredients.

ISOPROPANOL

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues).

SECTION 14: Transport information

General This product is packed in accordance with the Limited quantity Provisions of CDGCP2, ADR and IMDG. These provisions allow the transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing they are labelled in accordance with the requirements of those regulations to show that they are transported as Limited Quantities. Aerosols not so packed must show the following.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



ADR/RID class 2, 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Health and Safety at Work etc. Act 1974 (as amended).
Control of Substances Hazardous to Health Regulations 2002 (as amended).
The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures
according to Regulation (EC)
1272/2008

Aerosol 1 - H222, H229: Weight of evidence.
Eye Irrit. 2 - H319, STOT SE 3 - H336: Calculation method.

Issued by

Technical Service Manager

Revision date

20/07/2018

Revision

4



MATERIAL SAFETY DATA SHEET

STOVE CARE GLASS CLEANER



Supersedes date	07/10/2014
SDS number	11381
Hazard statements in full	<p>H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.